



Safety Data Sheet

Issuing Date: November 6, 2014

Revision Date: August 30, 2024

Revision Number: 3

1. Identification of the Substance/Preparation and the Company Undertaking

GHS Product Identifier

Product Name Pump Action Ultra Violet Solvent Base Marker

Other Means of Identification

Part Number 04500 – UV Clear, Bulk
04550 – UV Clear, Carded

Colors: Clear (visible under black light)

Formula Code SKM104

Synonyms none

Recommended use of the chemical and restrictions on use

Recommended Use Marker

Uses Advised Against No information available

Supplier's Details

Supplier Address

SKM Industries Inc.
1012 Underwood Road
Olyphant, Pa 18447
Telephone: 570-383-3062

Emergency Telephone Number

Chemtrec US & Canada 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communications Standard 2012 (29 CFR 1910.1200)

Flammable Liquid Category 3

Skin Corrosion/Irritation Category 2

Serious eye damage/Eye Irritation Category 2A

Acute Toxicity Inhalation Category 4

Acute Toxicity Skin Category 4

Aspiration Hazard Category 1

Specific target Organ Toxicity (single Exposure) respiratory tract irritation Category 3

Specific target Organ Toxicity (repeated Exposure) Inhalation Category 2

GHS Label Elements, including precautionary statements

Emergency Overview

Signal Word – Danger

Hazard Statements –

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.
Harmful if inhaled.
Harmful in contact with skin.
May be fatal if swallowed and enters airways.
May cause damage to organs through prolonged or repeated exposure by inhalation.
Suspected of causing cancer if inhaled.
Flammable liquid and vapor.



Appearance – Opaque, varies
Physical state- Thin viscosity liquid
Odor – Aromatic Odor

Precautionary Statements

Prevention

Do not handle until all safety precautions have been read and understood
Obtain special instructions before use
Keep container tightly closed
Use only in a well ventilated area
Do not breathe dust/vapors/fumes
Wash face and hands and any exposed skin thoroughly after handling
Wear protective gloves/clothing/eye protection/face protection
Keep away from heat/sparks/flame hot surfaces – no smoking
Use explosion proof electrical/ventilating/lighting equipment
Ground/bond container and receiving equipment.
Use non sparking tools
Take precautionary measures against static discharge

Response:

If exposed or concerned: get medical attention/advice.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
If swallowed: Immediately call a poison center/doctor. Do not induce vomiting.
In case of fire: Use CO₂, dry chemical, foam or water spray to extinguish.

Storage:

Store in a well-ventilated place.
Keep cool.
Store locked up.
Keep container tightly closed.

Disposal

Dispose of contents/container in approved waste disposal plant.

General Advice

If exposed or concerned: get medical attention/advice

ACUTE HAZARD: At high concentration, dizziness and unconsciousness may occur.

CAUTION: Contains xylene. Harmful or fatal if swallowed. Avoid inhalation. Direct contact may cause skin or eye irritation.

KEEP OUT OF REACH OF CHILDREN.

Fire

Use CO2, dry chemical, foam, or water spray

Spills and Leaks

Contain and collect spillage

Hazard not Otherwise Classified (HNOC)

Not applicable

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS -No | Weight % | Trade Secret |
|---------------|-------------|----------|--------------|
| Xylene | 1330-20-7 | 10-60 | * |
| Resin | proprietary | 5-50 | * |
| Colorant | proprietary | 0-10 | * |

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

- General Advice** In case of doubt, or when symptoms persist, seek medical attention.
- Eye Contact** Immediately flush eyes with plenty of water for at least fifteen (15) minutes. Get medical attention immediately.
- Skin Contact** Flush skin with plenty of water. Remove contaminated clothing. Was skin thoroughly with soap and water or use a proprietary skin cleanser.
- Inhalation:** Remove to fresh air, keep patient warm and at rest. If breathing is irregular seek medical advice. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately.
- Ingestion** Seek medical attention immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Protection of First Aiders Use personal protection equipment.

Most important symptoms/effects, acute and delayed

Most important symptoms/effects No information available

Indication of immediate medical attention and special treatment needed, if necessary

Note to physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, carbon dioxide, regular foam. For large fires, use foam or flood with fine water spray

Unsuitable extinguishing media No information available

Specific Hazards arising from the chemical No information available

Flash Point: 79°F

Flammability Limits (% by volume): Lower 1.1%; Upper 6.4%

Unusual Fire Explosion Hazards: none

Protective Equipment and Precautions for Firefighters

Wear appropriate self-contained breathing apparatus MSHA/NIOSH (approved or equivalent) and full protective gear. Cool closed containers exposed to fire with water spray. Avoid inhalation of material or combustion by-products; stay upwind.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid breathing vapours. Evacuate personnel to safe areas. Ensure adequate ventilation.

Environmental Precautions Avoid release into the environment. Do not allow to enter drains or watercourses.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Contain the spillage with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth to soak up the product and place in a suitable container for disposal in accordance with the waste regulations

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid skin and eye contact. Avoid the inhalation of vapor and mist.

Conditions for safe storage, including any incompatibilities

Storage Keep away for open flame, hot surfaces and sources of ignition. Keep containers tightly closed. Observe label precautions. Store between 5-25° C in a dry, well ventilated place. Prevent unauthorized access.

Incompatible products Unknown

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------|-----------------------------|---|------------|
| Xylene 1330-20-7 | STEL 150 ppm TWL 100 ppm | TWA 100 ppm TWA 435mg/m3 Vacated TWA 100 ppm Vacated TWA 435 mg/m3 Vacated STEL 150 ppm Vacated STEL 655 mg/m3 | - |

Appropriate engineering controls

Engineering Measures Showers, eyewash stations, ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face protection None under normal use conditions

Skin and body Protection None under normal use conditions

| | |
|-------------------------------|--|
| Respiratory Protection | None under normal use conditions. If irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn |
| Hygiene Measures | Use in a well-ventilated area. When using do not eat, drink, or smoke. Provide regular cleaning of equipment, work areas and clothing. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| <u>Property</u> | <u>Value</u> |
|--|---|
| Boiling Point: | 282 to 286°F |
| Specific Gravity (H ₂ O=1) @70°F: | >1 |
| Vapor Pressure (mm-Hg @ 70°F): | No Data |
| Melting Point: | No Data |
| Vapor Density (AIR = 1): | Greater than one (1) |
| Evaporation Rate (Butyl Acetate = 1): | Less than one (1) |
| Solubility in Water: | Negligible |
| PH: | No Data |
| Appearance and Odor: | Opaque, thin viscosity liquid with aromatic odor. |
| Volatile Organic Compound: | 705 grams per liter |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | No data available |
| Chemical Stability | Stable under normal storage and handling conditions |
| Possibility of Hazardous reactions | None under normal use |
| Hazardous Polymerization | Will not occur |
| Conditions to Avoid | Heat, open flame, sparks, and sources of ignition |
| Incompatible Materials | Strong oxidizing and reducing agents, strong alkalis and strong acids |
| Hazardous Decomposition -products | Carbon dioxide, carbon monoxide, smoke, soot and various oxidation by-products. |

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|----------------------------|---|
| Product Information | None available. There is no data available on the product itself. |
|----------------------------|---|

12. ECOLOGICAL INFORMATION

| | |
|--------------------|--|
| Ecotoxicity | There is no data available on the product itself |
|--------------------|--|

13. DISPOSAL CONSIDERATIONS

| | |
|-------------------------------|--|
| Waste Disposal Methods | Dispose of in accordance with all applicable local, state and federal regulations. |
| Contaminated Packaging | Do not re-use empty containers. |

14. TRANSPORT INFORMATION

| | |
|--|----------|
| Domestic Highway (Containers <1 Quart are ORM-D) | |
| Proper Shipping Name: | Consumer |
| Commodity Hazard Class/Subsidiary: | ORM-D |

UN/NA No.: None
Packing Group: None
Label Required: ORM-D

15. REGULATORY INFORMATION

TSCA INVENTORY: The product on this SDS is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory.

US Regulatory Rules:

Section 313 or Title III of SARA. This product contains a chemical which is subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations Part 372.

Xylene 1330-20-7 10-40% wt

SARA 311-312 Hazard categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | YES |
| Chronic Health Hazard | YES |
| Fire Hazard | YES |
| Sudden release of Pressure Hazard | NO |
| Reactive Hazard | NO |

| | |
|----------------------------|------------|
| California Proposition 65 | NOT listed |
| MA Right to know List | Listed |
| New Jersey Right to Know | Listed |
| Pennsylvania Right to Know | Listed |

16. OTHER INFORMATION

Health Hazard 2 Flammability 3 Reactivity 0 Personal Protection B

SKM has been advised by attorney that the OSHA Hazard Communication Standard does not apply to the SKM products listed in this SDS. The explanation for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2002 per the code of Federal Regulations. This information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the Hazard Communication Standard covers the product nor is this SDS meant to comply with all requirements of the Hazard Communication Standard.

End of Safety Data Sheet